

## K-Lock® Wedge Skirting Clamp

### Reliable, Tool-Free Skirt Adjustment

In today's working environment dust and spillage is no longer acceptable. Therefore a reliable and efficient skirting clamp system needs to be considered, addressing the following factors.

Firstly, the system must be simple and adequate to withstand the potential abuse of adjustment. Secondly, it must be universal in its application to accept many forms of skirting materials and configurations. Finally, it must also be able to fit into tight locations whilst remaining serviceable.

The wear and tear of the skirting or sealing material will require the operator to provide continuous adjustment depending on the abrasive wear of the product or the design and functionality of the transfer point. If the skirting clamp is difficult to maintain then the necessary adjustment may not happen or promote over adjustment so that the pressure applied by the skirting seal damages the belt.

The K-Lock® Wedge Skirting Clamp fulfils the entire practical requirement of a reliable and serviceable system that is free of complications and the need for special tools to maintain correct seal pressure. Therefore any signs of dust can be taken care of during minor plant outages.

All components of the K-Lock® Wedge Skirting Clamp are hot dipped galvanised. Stainless steel options are available as well as customized configurations. Standard skirting rubber can be used without requiring bolt holes to be punched. The system includes all mounting hardware.

#### Key Benefits:

- Efficient skirting rubber adjustment
- Fits all rubber thicknesses
- Easy to install

Part Number	Skirt Rail Length (mm)	Retainer Plate Depth (mm)	Assembly Weight (kg)
K-SKI-KLOC75-AS	2400	75	12.9
K-SKI-KLOC100-AS	2400	100	15.4
K-SKI-KLOC150-AS	2400	150	19.4



# K-Lock® Wedge Skirting Clamp

